

Mapelatex 119: Product Information Sheet

Description:	Multipurpose latex additive for mortars and cementitious adhesive
Uses:	For the preparation of high-performance mortars, screeds and renders.
Some application examples:	▪ Screed and levelling compounds for interior and exterior use. ▪ Cement renders for interior and exterior use. ▪ Cement slurry for bonding new screeds for existing screeds and concrete. ▪ Cement-mortar adhesive for interior and exterior bonding of ceramic tiles on walls and floors. ▪ Modifying cement mortars that have to be applied in thin layers.
Consumption:	▪ Slurry bond coat / Spatter-dash coat- 0.3kg of Mapelatex 119 per m². ▪ Floor screed and wall plaster- 1kg of Mapelatex 119 per m² of 20mm thickness.
Packaging:	18 kg and 4 kg pail
Chemical Base:	Styrene-Butadiene Rubber (SBR)
Colours:	Milky White
Shelf Life:	12 months from the date of production

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION:

Mapelatex 119 is not considered as dangerous according to the current regulation regarding the classification of mixtures. We recommend to wear protective gloves and goggles and to take the usual precautions for handling chemicals.

For further and complete information about the safe use of our product please refer to our latest version of the Safety Data Sheet.

Important notes

- This product is intended for sale through retail outlets only. While the products in our retail range are designed with knowledge gained from extensive project experience and conform to the highest MAPEI quality standards, they are not intended for use in commercial-scale projects. Therefore, no technical support will be attendant on the sale of these products.
- For product recommendations in projects requiring technical support and attendance, please contact MAPEI at mapei@mapei.com.my.